

Electric Lock

Electric Strike

AI-130NO/NC

- Standard, concealed installation
- Power-off to lock(NO) Power-on to lock(NC
- Working Voltage: DC12V input
- Working Current: 240mA(NO) 120mA(NC)
- Holding Force: 250kg
- Weight: 0.37kg
- Lock jaw size: 29×17×11mm
- Lock body size: 150×28×35mm
- Suitable for: Wooden door
- Fail Secure/Fail Safe

AI-132NO/NC

- Special, wide-mouthed, concealed installation
- Power-off to lock(NO) Power-on to lock(NC)
- Working Voltage: DC12V input
- Working Current: 240mA(NO) 120mA(NC)

- Lock body size: 240x25x35mm
- Suitable for: Metallic door
- Fail Secure / Fail Safe

AI -100

- Concealed installation
- Power-on to lock, Door status signal NC output
- Working Voltage: DC12V input
- Working Current: 350mA
- Holding Force: 1000kg
- Weight: 0.72kg
- Size: 200×35×38mm



AI-300

- Wide-mouthed, concealed installation
 - Power-off to lock(NO) Power-on to lock(NC)
 - Working VoltageDC12V input
 - Working Current240mA(NO) 120mA(NC)
 - Holding Force: 400kg
 - Weight 0.38kg
 - Lock jaw size 45×17×11mm
 - Lock body size 150×28×35mm
 - Suitable for: Metallic door
 - Fail Secure/Fail Safe
 - concealed installation Power-on to lock
 - Working Voltage: DC12V input
 - Working Current: 240mA(NO) 120mA(NC)
 - Holding Force: 250kg Weight: 0.37kg
 - Lock jaw size: 29×13×11mm
 - Lock body size: 150×28×35mm
 - Suitable for: Metallic door
 - Fail Safe
 - Concealed installation
 - Power-on to lock, lock status LED display,
 - Door status signal NC output
 - Working Voltage: DC12V input • Working Current: 350mA
 - Holding Force: 1000kg
 - Weight: 0.77kg

 - Size: 200×35×38mm

AL-100PF



- Electric bolt bracket in frameless glass door
- For installation of the drop bolt
- 8 -12mm thick frameless glass doors

AL-200PZ



- · Electric bolt bracket in frameless glass door
- For installation of lock
- 8 -12mm thick frameless glass doors

AL-131NO/NC



AI -133NC







Electromagnetic Lock

AI-180M



- Power-on to lock
- Holding Force: 150kg
- Working Voltage: DC12V/24V input
- Weight: 1.02kg
- Size: 198×21×35mm



- Power-on to lock Working
- Voltage: DC12V/24V input
- Holding Force: 150kg

AI-180

- Weight: 1.07kg
- Size: 166×21×41mm

AI-180D



- Power-on to lock Working
- Voltage: DC12V/24V input
- Holding Force: 2×150kg
- Weight: 2.15kg
- Size: 332x21x41mm

AL-280(LED)

AL-350(LED)



- Power-on to lock Holding Force: 270kg
- Working Voltage: DC12V/24V input
- Weight: 1.97kg
- Size: 253×25×48mm

AL-350D(LED)

AL-280D(LED)

- Power-on to lock Holding Force: 300kg
 - Working Voltage: DC12V/24V input
 - Weight: 2.46kg
 - Size: 253×28×55mm



- Power-on to lock Holding Force: 2×270kg
- Working Voltage: DC12V/24V input
- Weight: 3.90kg
- Size: 506×25×48mm
- Power-on to lock Holding Force: 2×300kg
- Working Voltage: DC12V/24V input
- Weight: 4.92kg
- Size: 506×28×55mm

AL-500(LED)



- Power-on to lock
- Holding Force: 500kg Working Voltage: DC12V/24V input
- Weight: 4.48kg
- Size: 280×38×70mm



- Power-on to lock
- Holding Force: 2×500kg
- Working Voltage: DC12V/24V input
- Weight: 8.96kg • Size: 560×38×70mm

Electric Cabinet Lock

AL-400



- Electric lock for storage box
- Power Supply: DC 12V 0.6A
- Dimension: 54.5mm×41mm×28mm



- AL-500D(LED)

Brackets for electromagnetic locks

AL-180/280/350PL



- L bracket for AL180/280(LED)/350(LED)
- $\boldsymbol{\cdot}$ To install the lock body

AL-180/280/350DPL

AL-500PL



- L bracket for AL-500(LED)
- To install the lock body

AL-500DPL



- L bracket for AL180D/280D(LED)/350D(LED)
- To install the lock body



- L bracket for AL-500D(LED)
- To install the lock body

AL-350PU



- U bracket for AL-350/350D
- To intall the iron plate on the glass door (the lock body install on the frame door)

AL-500PZ



• Z bracket for AL-500(LED)/AL-500D(LED) • To install the iron plate



AL-180/280PU

U bracket for AL180/280/180D/280D
To intall the iron plate on the glass door (the lock body install on the frame door)

AL-180PZ



Z bracket for AL-180 To install the iron plate

AL-500PU



U bracket for AL-500/500D
To intall the iron plate on the glass door (the lock body install on the frame door)

AL-280/350PZ



- Z bracket for AL-280(LED)/AL-280D(LED)/ AL-350(LED)/AL-280D(LED)
 To install the immediate
- To install the iron plate

ZKTeco Europe

E-mail: sales@zkteco.eu www.zkteco.eu © Copyright 2014. ZKTeco Inc. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

