





Key Features

- ◆H.264 (high definition)
- ◆720P full real time recording
- ◆Conforms to ONVIF
- ◆Support mobilephone, IE browser
- ◆3D bracket adjustable,
- ◆Vandal-proof, IP66, Lighting-proof, DC12V

Dimension



WIRE INTERFACE

1. Power Supply
2. Network Interface



SPECIFICATION

Model	PS-621HD
Parameter	1/4" OV 1.3 mega Progressive scan CMOS
Camera	
Sensor	1/4" OV 1.3 mega Progressive scan CMOS
Min. Illumination	0Lux/F1.4
Electronic shutter	Auto/Manual (1/25~1/10000)
Day/Night	Auto/B/W/Color/EXT ICR switching
Video Parameter	DWDR, Mirror, 3D Noise reduction, Sharpness/Lightness adjustable
IR Distance	10-15M(24*Φ5 IR leds)
Lens	3.6mm M12 2Mega lens
Lens interface	M12
AUDIO/VIDEO COMPRESSION	
Video compression	H.264
Encoding Features	Dual-stream; Main stream PAL: 1280X720 25fps; NTSC:1280X720 30fps
Max. resolution	1280X720
Encoding System	Constant bit rate, Variable bit rate optional
Video Bit rate	1024Kbps-6144Kbps
Stream Type	Complex stream/Video stream
Audio Compression	G.711A
Audio Bit rate	64Kbps
NETWORK	
Password protection	Support
Character display	Support (Channel, Date)
Alarm function	Video loss, Network disconnect, Tampering alarm, Storage exception
Mobile surveillance	Apple, Android
Protocol	TCP/IP,UDP,HTTP,DHCP,RTP/RTSP,DNS,DDNS,NTP,PPPOE,UPNP,SMTP
Port protocol	18, ONVIF
INTERFACE	
Network Interface	RJ45 10M/100M adaptive
GENERAL	
Operating Conditions	-10°C ~ 55°C/0% -90%
IP Grade	IP66
Power Supply	DC12V & POE
Power Consumption	<5W
Dimensions	83.3(H)*93(D)mm
Weight	300g
WIRE INTERFACE	
1、Power Supply	
2、Network Interface	