

DS-7700NI-I4 SERIES NVR



Features and Functions

Professional and Reliable

- Dual-OS design to ensure high reliability of system running. The system has Linux embedded with the Pentaplex function
- The system has language: Portuguese and English
- HDD hot swap with RAID0, RAID1, RAID5, RAID6 and RAID10 storage scheme configurable
- Support different levels of the user with the possibility of the lock cameras for the user. Support 10 user connection in the same time. Support, remote configuration of the system, playback, download, log of the system, update of the device and cameras. Update of the firmware by local system and remote system. Backup of the configuration file.

Video Input and Transmission

- Up to 32-ch 12 MP IP cameras can be connected with control of the bit rate per channel. Network interface control
- Real time live view and playback. Web Server with remote access . Format of the video AVI, ASF.

Compression and Recording

- H.264+ compression effectively reduces the storage space and costs by up to 50%
- Full channel recording at up to 12MP resolution.

Storage and Playback

- Up to 4 SATA interfaces and 1 eSATA interface connectable for recording and backup
- Smart search for efficient playback. Backup by USB interface, by networking and FTP.
- 8/16-ch synchronous playback at up to 1080p resolution with the option to search by date, hour, seconds and motion detection. Support zoom digital in the camera and playback.

Smart &POS Function

- The system possibility: live view, playback, record, backup and remote access in the same time.
- Functions: motion detection, loss video, masking of the camera, and offline camera.
- Support of the visualization of the: name of camera, hour, date, record status, motion detection, loss video, lock of the camera, status of the HD, statics of the transmission, log of the events, firmware version, online users and input 4 regions of the mask private

Network & Ethernet Access


- Hik Cloud P2P & HiDDNS (Dynamic Domain Name System) for easy network management. IVMS 4200 free included.



| Model | | DS-7708NI-I4 | DS-7716NI-I4 | DS-7732NI-I4 |
|--------------------|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|-------------------------------------|
| Video/Audio input | IP video input | 8-ch | 16-ch | 32-ch |
| | | Up to 12 MP resolution | | |
| | Two-way audio | 1-ch, RCA (2.0 Vp-p, 1 kΩ) | | |
| Network | Incoming bandwidth | 80 Mbps | 160 Mbps | 256 Mbps |
| | Outgoing bandwidth | 256 Mbps | | |
| | Remote connection | 32 | 128 | |
| Video/Audio output | Recording resolution | 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF | | |
| | CVBS output (Optional) | 1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480 | | |
| | HDMI output resolution | 4K (3840 × 2160)/60Hz, 4K (3840 × 2160)/30Hz, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz | | |
| Decoding | VGA output resolution | 1920 × 1080p/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz | | |
| | Mode of the view | Mosaic with the mode 1, 4, 8, 9 and 16 | | |
| | Decoding format | H.265/H.265+/H.264/H.264+/MPEG4/MJPEG | | |
| | Live view / Playback resolution | 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF | | |
| Network management | Synchronous playback | 8-ch | 16-ch | 32-ch |
| | Rate recording frame rate | 2-ch @ 4K, or 8-ch @ 1080p – 30fps | 4-ch @ 4K, or 16-ch @ 1080p – 30fps | 4-ch @ 4K, or 32-ch @ 1080p – 30fps |
| | Network protocols | IPV4 and IPV6, TCP/IP, DHCP, HIK Cloud P2P (DDNS of the Hikvision), DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS, ONVIF, DYNDNS, NO-IP, FTP, IP filter, HTTP, RTSP, search IP, alarm server, UDP, PPPoE. Send email for 3 differents addres with alerts and photos. Alarm of the disconnect networking | | |
| Hard disk | SATA | 4 SATA interfaces for 4HDDs | | |
| | Capacity | Up to 6TB capacity for each HDD | | |
| | Functions | Manager HD, error of the record, limited of HD, erro HD. Search of the events: Motion detection, alarm, regular with the hour and date precision. Tags for the mark of the events, 5 speeds of the playback and selection of the file to playback. | | |
| External interface | Network interface | 2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface, with the possibility to have redundancy networking. | | |
| | Serial interface | 1 RS-485 (half-duplex), 1 RS-232 | | |
| | USB interface | Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0, backup of the image by HD external and drive DVD-RW | | |
| | Alarm in/out | 16/4 | | |
| General | Power supply | 100 to 240 VAC with 60hz | | |
| | Power | ≤80 W | | |
| | Consumption (without hard disk) | ≤20 W | | |
| | Working temperature | -10 to +55° C (+14 to +131° F) | | |
| | Working humidity | 10 to 90 % | | |
| | Chassis | 19-inch rack-mounted 1U chassis | | |
| | Dimensions (W × D × H) | 385 × 315× 44.45 mm (15.2" 12.4" 1.75") | | |

| | | | |
|--|---------------------------------------|----------------|--|
| | Weight (without hard disk) | ≤ 5 kg (11 lb) | |
|--|---------------------------------------|----------------|--|

Physical Interfaces



| Index | Description | Index | Description |
|-------|--------------------------|-------|-------------------------------------|
| 1 | LAN1 and LAN2 Interfaces | 7 | VGA Output (DB9 Connector) |
| 2 | AUDIO OUT | 8 | RS-485 Serial Interface |
| 3 | AUDIO IN | 9 | Controller Port, Alarm In/Alarm Out |
| 4 | HDMI Interface | 10 | GND |
| 5 | USB 3.0 Interface | 11 | 100 to 240 VAC power supply |
| 6 | RS-232 Serial Interface | 12 | Power Switch |

Available Models

DS-7708NI-I4, DS-7716NI-I4, DS-7732NI-I4

Distributed by



Headquarters
No.556 Shennan Road, Binjiang District
Hangzhou 310051, China
T: +86 571 8907 5999
sales@ Hikvision.com

Hikvision USA
T: +1 800 828 0100
salesusa@ Hikvision.com

Hikvision Italy
T: +39 0438 8902
info.it@ Hikvision.com

Hikvision Singapore
T: +65 6594 1718
sg@ Hikvision.com

Hikvision Africa
T: +27 (0) 025 1172
sales.africa@ Hikvision.com

Hikvision Europe
T: +31 20 25 72 770
info.eu@ Hikvision.com

Hikvision France
T: +33 (0) 1 69 630 450
info.fr@ Hikvision.com

Hikvision Oceania
T: +61 2 8589 4233
sales.au@ Hikvision.com

Hikvision Hong Kong
T: +852 2331 1781

Hikvision Middle East
T: +971 4 551 8056
sales.me@ Hikvision.com

Hikvision Spain
T: +34 91 737 16 52
info.es@ Hikvision.com

Hikvision Canada
T: +1 800 825 8700
sales.us@ Hikvision.com

Hikvision Russia
T: +7 495 660 57 99
sales.ru@ Hikvision.com

Hikvision Poland
T: +48 22 460 01 59
poland@ Hikvision.com

Hikvision Korea
T: +82 31 731 8841
sales.korea@ Hikvision.com

Hikvision India
T: +91 22 28400100
sales@ pteahikvision.com

Hikvision UK
T: +44 1828 852148
support.uk@ Hikvision.com

Hikvision Brazil
T: +55 11 3318 0050
latam.support@ Hikvision.com