ZOR702VW The Most Durable CCTV Camera

INNEKTInnovative Technology

Vandal Proof Dome Camera

- 1/3" 960H SONY Super HAD CCD II for 700 TV Lines
- Super Wide Dynamic Range by SONY Effio-P DSP
- Aluminum alloy housing design for outdoor
- Wide input voltage (DC 9-20V)
- Anti-Exposure IR night vision
- 24 IR LEDs with IR distance 20M
- High efficiency 850nM 30deg.,IR LED
- High definition manul 4.0 9.0mm vari-focal lens
- Constant current circuit for long life IR
- FCC, RoHS, CE Certified

























Dimensions (unit : mm)





Specification

Model		ZOR702VW
Signal System		PAL
Image Sensor		1/3" 960H Sony Double Scan Super HAD CCD II
Scanning System		2:1 Interlaced
Scanning Frequency		H: 15.625 KHz, V: 50 Hz
Total Pixels		1028(H) x 596(V)
Effective Pixels		976(H) x 582(V)
Resolution		700 TV Lines
Electronic Auto Shutter		1/50 - 1/100,000 sec automatic
S/N ratio		More than 50 dB (AGC Off)
Sensitivity		0.001Lux at F1.2 / 0 Lux (IR LED On)
Gamma correction		r = 0.45
Synchronize System		Internal
Video Output		1 Vp-p 75 ohm Composite
OSD Control		Joystick
Multiple Language OSD		English, Japanese, Chinese
EZOOM		Picture Magnification (x255), Pan/Tilt (Must magnify the picture first)
Back Light Compensation		Off, BLC, HLC
White balance	ATW	Auto.1800°K - 10500°K
	Selectable	ATW, Push, User1, User2, Anti-CR, Manual, Push Lock
Wide Dynamic Range		FULL, Normal, Light (Adjustable by control Contrast Level)
3D Noise Reduction		OFF, LOW, MIDLOW, MID, MIDHIGH, HIGH
Day / Night		ICR Moving Filter Mechanism (optional)
Motion Detection		4 Zones
Privacy Masking		Upto 15 Zones
Digital Effects		Digital Image Stabilization / Mirror / Contrast / Sharpness etc
Lens		f4.0 - 9.0mm Vari-Focal Iris Lens
IR LED		24 IR LEDs, Up to 20M Range
IR LED Operation		On (1Lux) / Off (1Lux)
IP Rating		IP66 Waterproof
Power Supply		DC12V (Tolerance DC9~20V)
Operating current		400mA w/regulated power in
Operating Temperature		14°F ~ 122°F(-10°C ~ +50°C)
Storage Temperature		-4°F ~ 140°F(-20°C ~ +60°C)
Dimenssion(mm)		160(W) x 127(H)
Weight(Approx.g)		1740g

FC RoHS (