

MDR752HA-B











4CH Full 960H DVR

FEATURES

Push Video & Push Status - Active Event Notification with EagleEyes App

- Push Video to send instant notifications for an alarm event when an alarm device is connected to the DVR.
- Push Status to send instant notifications for system events, such as video loss or HDD data removal.



All-Channels 960H Video Recording

Supports 960H video recording for all channels for evidentiary recording with high quality and clear images.



HDMI Video Output at 1080P Resolution

Full HD video display through HDMI interface.

Mobile Surveillance with EagleEyes App

Compatible with iOS & Android mobile devices.

Remote Surveillance with Browsers and CMS

- For web browsers, compatible with Internet
 Explorer, Mozilla Firefox, Google Chrome & Safari
- For CMS software, available with our self-developed and free software, "Video Viewer.
- Applicable also to Apple's media player, QuickTime.

External Disk Array Support for More Video Storage

eSATA interface built-in to connect a disk array (up to 4-bay disk array with RAID 0 and 1) for more video storage.

Independent Channel Control

Definable "Resolution" / "Quality" / "IPS" by channels at your preferences to increase the recording efficiency, and avoid any important scenes to be missed.

Remote Independent Operation

Channel switching is independent from the local site, allowing users to have private image monitoring remotely.

Multiplex

Allows live display, record, playback, backup and network operation at the same time.

Backup Function

Supports USB flash drive and network backup.





SPECIFICATIONS

▼ Video				
Video System			NTSC / PAL (auto detection)	
Video Compression Format			H.264	
Video Input			4 channels (Composite video signal 1 Vp-p 75Ω BNC)	
Video Output	VGA		YES	
vidoo odipui	HDM	l	YES	
	BNC		YES (Main monitor for stable display)	
Dual Video Output			YES	
▼ Record & Bac	kup			
Maximum Recording Rate F G		960H	960x480 pixels with 120 IPS <ntsc> / 960x576 pixels with 100 IPS <pal></pal></ntsc>	
		Frame	704×480 pixels with 120 IPS <ntsc> / 704×576 pixels with 100 IPS <pal></pal></ntsc>	
		Field	704x240 pixels with 120 IPS <ntsc> / 704x288 pixels with 100 IPS <pal></pal></ntsc>	
		CIF	352×240 pixels with 120 IPS <ntsc> / 352×288 pixels with 100 IPS <pal></pal></ntsc>	
		Oil	Manual / Timer / Motion / Alarm / Remote	
Recording Mode Pre-alarm Recording			YES	
Quick Search			Time / Motion / Alarm search mode	
			USB 2.0 flash drive / Network	
Backup Device V Audio			2.0 Hasti diive / Network	
			A south is south	
Audio Input			4 audio inputs	
Audio Output			1 audio output (Mono)	
▼ General				
Hard Disk Storage			Accommodates up to 1 SATA HDD (1 HDD capacity up to 4TB)	
SATA Interface			YES	
eSATA Interface			YES (For external disk array connection)	
Image Quality Setting			SUPER BEST / BEST / HIGH / NORMAL	
USB Mouse Control			YES	
Motion Detection Area			16 x 12 grids per channel	
Motion Detection Sensitivity			3 adjustable parameters for accurate detection	
Event Notification			Push Video / FTP / E-Mail	
Picture Zoom			2X digital zoom	
PTZ Control			YES	
Alarm I/O			4 inputs (1 input for Push Video), 1 output	
IR Remote Control			YES (IR receiver built-in)	
Key Lock (Password Protection)			YES	
User Level			4 user levels for different access privilege	
Video Loss Detection			YES	
Camera Title			Supports up to 12 letters	
Video Adjustable			Hue / Saturation / Contrast / Brightness	
Date Display Format			YY/MM/DD, DD/MM/YY & MM/DD/YY	
Daylight Saving			YES	
Power Source (±10%)			DC19V / 2.1A	
Power Consumption (±10%)			5W (without hard disk & camera)	
Operating Temperature			10°C ~ 40°C (50°F~104°F)	
Dimensions (mm)**			375(W) × 61(H) × 281(D)	
▼ Network				
Ethernet			10/100 Base-T. Supports remote control and live view via Ethernet	
Network Protocol			TCP/IP, PPPOE, DHCP and DDNS	
INGLWOIK I TULUUUI			TOLAN , THE OL, DITOL AND DONO	





SPECIFICATIONS

Compatible Operating System	Windows & MAC		
Compatible Program	Web Browser:	Internet Explorer, Mozilla Firefox, Google Chrome & Saf	
	Video Viewer:	For both Windows and MAC operating systems	
	QuickTime	For both Windows and MAC operating systems	
Max. online users	10		
Web Transmitting Compression Format	H.264		
Network Live Audio	YES		
Remote Independent Operation	YES		
Remote Event Download & Playback	YES		
R.E.T.R. (Remote Event Trigger Recording)	YES		
▼ Mobile Surveillance			
Арр	EagleEyes		
Compatible Devices	iOS & Android devices		
Push Video & Push Status	YES (With EagleEyes for iOS & Android devices)		
▼ Others			
AVTECH Free DDNS service	YES		
Multiplex Operation	Live display / record / playback / backup / network operations		
System Recovery	System auto recovery after power failure		
Optional Peripherals	Keyboard Controller		

*The specifications are subject to change without notice.

** Dimensional tolerance: ±5mm

REAR PANEL

