

KPC133D

21 LEDs Dome Camera



● FEATURES



- (1) High sensitivity in the dark environment, 0.05Lux / F2.0, 0Lux (IR ON)
- (2) Day and night features for 24-hour surveillance
- (3) Excellent image quality
- (4) IR LED effective range reaches up to 15 meters



● SPECIFICATIONS*

| MODEL | KPC133D |
|----------------------------|--|
| Pick up Element | 1/3" color CCD image sensor |
| Number of Pixel | 512(H) x 492(V) <NTSC> / 512(H) x 582(V) <PAL> |
| Resolution | Standard |
| Min. Illumination | 0.05Lux / F2.0, 0Lux (IR ON) |
| IR LED | 21 units |
| Effective Range | Up to 15 Meters |
| S/N Ratio | More than 48dB (AGC off) |
| Electronic Shutter | 1/60 (1/50) to 1/100,000 sec. |
| Lens | f3.6mm / F2.0 |
| Lens Angle | 92.6° |
| IRIS Mode | AES |
| White Balance | ATW |
| Video Output | 1.0 Vp-p composite, 75Ω |
| Power Source (±10%) | DC12V |
| Current Consumption (±10%) | 70mA (IR OFF), 210mA (IR ON) |

* The specifications are subject to change without notice.

** Dimensional Tolerance: ± 5mm

| Good Sensitivity in Low Illumination | |
|---|---|
| KPC13x Series | Conventional |
|  |  |

| True Color | |
|--|---|
| KPC13x Series | Conventional |
|  |  |